



Info
Status
Wi-Fi scan

Profiles

IP settings
Radio settings
Serial settings
Advanced settings
Dynamic DNS settings
Keyer settings
IO settings
Ping settings
Wi-Fi settings

Export settings(HTML)
Export settings(bin)
Import settings(bin)

Application upgrade
Bootloader upgrade

Restart device

Radio settings

Program mode

Sip password

Sip contact

Auto connect

Audio quality

Codec out gain

Codec inp gain

Codec inp HPF Hz

Codec inp preamp

COM0 baudrate

COM0 data bits

COM0 stop bits

COM0 parity

COM0 Program mode 3 char timeout

Use USB Com Port as COM0

Settings help

Baudrate	Radio
9600	IC-R2500
19200	IC-706, FT-8800/8900
38400	IC-7100, IC-2820, DX-SR8
48000	FTM-350
57600	TS480, TS2000, TM-D710
64000	FT-100, FT-857



Info
Status
Wi-Fi scan

Profiles

IP settings
Radio settings
Serial settings
Advanced settings
Dynamic DNS settings
Keyer settings
IO settings
Ping settings
Wi-Fi settings

Export settings(HTML)
Export settings(bin)
Import settings(bin)

Application upgrade
Bootloader upgrade

Restart device

Serial settings

COM1 mode	Mode-7, CAT to COM2 (remote) ▼
COM1 baudrate	9600 ▼
COM1 data bits	8 ▼
COM1 stop bits	1 ▼
COM1 parity	0 - Off ▼
COM1 rts/cts	No ▼
COM1 terminator (hex)	00
Use USB Com Port as COM1	Yes ▼
COM2 mode	Logical parallel with COM0 ▼
COM2 baudrate	38400 ▼
COM2 data bits	8 ▼
COM2 stop bits	1 ▼
COM2 parity	0 - Off ▼
COM2 terminator (hex)	00
Use USB Com Port as COM2	No ▼
COM3 mode (USB-COMFSK)	Mode-10, Baudot-RTTY ▼

Submit

Apply changes

Settings help











